

CE PRODUCT DATA SHEET

* VOC COMPLIANT SOLVENT BLEND * HIGH OLEOPHOBIC SOLID CONTENT *

* FULL MANUFACTURER MATERIAL AND LABOR WARRANTY AVAILABLE *

S.T.T. Sealers with Attitude!® Revision 12/2010



5 Space Drive Taylors, S.C.29687

Color Enhancing Sealer Product Data Sheet

Product Benefits

- .Enriches color without using harsh chemicals
- .Very low odor allowing use in residential settings
- .Applying more layers enrich the surface more.
- .Protects against both water and oil based stains
- .May be used with FE-Treatment for better protection.
- .Great for back splash edges.
- .Other formulas available, please call manufacturer for details.

Directions:

Read entire label and follow directions.
Test in a small inconspicuous spot and allow 24 hours to pass to assess product effectiveness. Grout should be installed for 72 hours before using CE-Color Enhancing Sealer. Make sure surface is clean, dry and free of waxes.
Wear appropriate safety gear including eyewear and gloves. Ventilate area during application and while product is drying.
Keep off the surface until the product is dry.
Keep product out of CHILDRENS' reach.

- 1) Shake well. Apply evenly and liberally with either a paint pad, roller, brush, or pump up chemical resistant coarse sprayer.
- 2) If the material is especially absorbent apply SB-Econo 1st to control against splotchiness. Once CE-Color Enhancing Sealer is applied, wait 15-30 minutes for it to absorb. Denser materials will take longer.
- 3) Additional coats may be applied in 24 hour intervals.
- 4) Full cure occurs 24-72 hours after completion.
- 5) Protect surface with brown kraft paper when finished.

Emergency and First Aid:

INGESTION: Do not induce vomiting. Call a poison control center, call a Doctor.

EYE CONTACT: Flush with water for 15 minutes. If wearing contacts, remove them after 5 minutes and continue flushing for 15 minutes.

SKIN CONTACT: Wash with mild soap and water. Call a Doctor if irritation persists.

INHALATION: Remove to fresh air. Call a Doctor if respiratory irritation persists.

STORAGE AND HANDLING:

CAUTION: Harmful if swallowed. May cause eye irritation. Don't swallow or ingest. Avoid prolonged exposure to vapors. Don't store above 100° F. Don't mix with other chemicals. Don't release into waterways.

Recommended Surface

All textures and finishes of natural stone, concrete ceramic tile, grout, and other masonry products.

Available Sizes

Quart cases, Gallon cases, 5-Gallon bucket, 55-Gallon drum

Technical Information

Form: Liquid

Flash & Boiling points: >212° F.

Freeze Point: <32° F.

VOC compliant

Coverage: 50-250 Square feet per gallon

Warranty term: 5 years counters, 2 years floors, 1 year showers. Longer on approval

Before

After

